

MATERIAL SAFETY DATA SHEET
STICK FAST™ DRYING AGENT – Dry Pak**EMERGENCY PHONE: 1-888-932-0405****1. GENERAL INFORMATION:**

Product name:	Drying Agent / Desiccant / Desiccare Silica Gel-TS6
Manufacturer:	Desiccare, Inc.
Chemical name:	Synthetic Silica Gel
Trade name:	Silica Gel-TS6
Chemical Family:	SiO ₂ · xH ₂ O
CAS Registry No:	63234-67-4
DOT Hazard Class:	N.A.
DOT Shipping Name:	N.A.
Product Name:	Synthetic Indicating Blue Silica Gel
Manufacturer:	Desiccare, Inc.
Chemical Family:	Silica gel impregnated with less than 1% cobaltous chloride.
DOT Hazard Class:	N.A.
DOT Shipping Name:	N.A.

2. Hazardous Ingredients

Material Formula	WT%	ACGIH TLV-TWA(OSHA-PEL)
Silica Gel	95-100	10mg/m ³ Total Dust
SiO ₂ · xH ₂ O		NIA*
Amorphous		

3. Physical Data:

Melting Point F>2900:	Bulk Density > 43 LB/FT
Melting Point F>1600:	Percent Volatiles By Weight <10 1750F
Appearance and Odor:	White beads or granulates; odorless

4. FIRE AND EXPLOSION HAZARD DATA:

Flash Point:	Non-flammable
Flammable Limits:	Negligible fire and explosion hazard when exposed to heat, flame
Extinguishing media:	Dry chemical, water spray or foam

MATERIAL SAFETY DATA SHEET

STICK FAST™ DRYING AGENT – Dry Pak

EMERGENCY PHONE: 1-888-932-0405

5. HEALTH HAZARD DATA:

Not considered a health hazard. When used in accordance with the instructions and the contents are not removed from the inner package, no masks or special equipment is required. Considered a minor irritant if comes in contact with skin or eyes. Wear protective mask if dust is present.

First Aid Eye:	Flush eyes with water for approximately 10 minutes while holding eyelids open. Seek medical attention if irritation or soreness persists.
Skin:	First aid is normally not needed. As a precaution, brush powdered material from the skin and wash with soap and water.
Inhalation:	Remove from exposure area to fresh air. Seek medical attention if any symptoms persist.
Ingestion:	If swallowed, as a precaution, rinse mouth with water. Do not induce vomiting; Seek medical attention if any symptoms persist.

6. REACTIVITY DATA:

Reactivity – Is stable under normal temperature and pressure in sealed container. Moisture can cause a rise in temperature, which can result in a burn.

7. SPILL OR LEAK PROCEDURES:

Notify safety personnel of leaks and spills. Clean-up personnel need protection against inhalation of dust and fumes. Eye protection is required. Vacuuming and/or wet methods of cleanup are preferred. Place in appropriate containers for disposal keeping airborne particulates at a minimum.

8. SPECIAL PROTECTION INFORMATION:

Respiratory:	Provide a NIOSH/MSHA jointly approved respiratory in the absence of proper environmental control. Contact your safety equipment supplier for proper mask type.
Ventilation:	Provide general and/or local exhaust ventilation to keep exposures below the TLV>Ventilation used must be designed to prevent spots of dust accumulation or recycling of dusts.
Protective Clothing:	Wear protective clothing, including long sleeves and gloves, to prevent rejected or prolonged skin contact.
Eye Protection	Chemical splash goggles designed in compliance with OSHA regulations are recommended. Consult your safety equipment supplier.

MATERIAL SAFETY DATA SHEET
STICK FAST™ DRYING AGENT – Dry Pak

EMERGENCY PHONE: 1-888-932-0405

9. SPECIAL PRECAUTIONS

Avoid breathing dust and prolonged contact with skin. Causes eye irritation and breathing dust may be harmful.

Keep away from children.

DISCLAIMER

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use